

## Compressoare

		Caracteristici	
	Serie	Presiune Maxima	Capacitate de compresie
GX 4 FF montat pe butelie de 200l	AII 643461	10 bar	7.8 l/s
GA 7 FF	AII 133826	8.5 bar	17 l/s
GA 18 SP	AII 240349	10 bar	43.5 l/s
GA 22 P	AII 281362	7.5 bar	51.7 l/s
GA 37+ P	API 510130	7.5 bar	116.2 l/s
GA 45 P (2BUC)	API 532472/API 532473	7.5 bar	138.8 l/s
GA 55 FF	API 616784	7.5 bar	166.7 l/s
GA 55 VSD FF	API 573057	7.5 bar	166.7 l/s
GA 75+ FF	API 602242	8 bar	200.2 l/s

## Pompe de vacuum

		Caracteristici	
	Serie	Frecventa de functionare	Debitul nominal
GHS 585 VSD+	API 850962	20-150 Hz	560 m <sup>3</sup> /ora
GHS 1600 VSD+	API 164975	20-200 Hz	1590 m <sup>3</sup> /ora

## Uscătoare

		Caracteristici	
	Serie	Presiune maxima	Capacitate de uscare
FD 60	AIQ 554559	13 bar	60 l/s
FD 65	CAQ 315654	13 bar	65 l/s
FX 12	CAI 235886	13 bar	138 l/s
FX 15	CAI 417047	13 bar	270 l/s

## Utilaje

mini excavator Komatsu PC14R

mini incarcator Komatsu SK510

platforma de ridicare cu brat (PRB) Iveco Daily cu brat de 10m